



BAPTISTRY SPECIFICATIONS

1.0 GENERAL

1.1 DESCRIPTION

- A. Baptistry shall be prefabricated of fiberglass reinforced polyester as manufactured by Campbellsville Industries, Inc., Model # _____.
- B. Baptistry shall be equipped with Accessory Package # _____ with a 5.5 or 11 KW heater.

1.2 QUALITY ASSURANCE

Manufacturer Qualification: Manufacturer shall have been regularly engaged in the manufacture of FRP baptisteries for a minimum of ten years and shall have a history of successful performance.

1.3 SUBMITTALS

Submit manufacturer's specifications, product data, shop drawings, and color samples upon request, prior to fabrication of unit.

1.4 DELIVERY, STORAGE, AND HANDLING

- A. Owner or contractor shall provide sufficient labor and equipment to unload product(s) upon delivery.
- B. Once delivered, the product(s) should be handled with proper equipment and stored in such a way as not to cause damage to the unit(s).

2.0 PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

Campbellsville Industries, PO Box 278, Campbellsville, KY 42718
Telephone: 800-467-8135 Fax: 270-465-6839
Website: www.cvilleindustries.com; E-mail: steeple@cvilleindustries.com

2.2 MATERIALS

- A. Fiberglass reinforced polyester shall have properties within the following ranges:

Flexural Strength	ASTM D-790	18,000 – 29,000 psi
Tensile Strength	ASTM D-790	18,000 – 29,000 psi
Compressive Strength	ASTM D-790	18,000 – 29,000 psi
- B. Unit shall be adequately reinforced to prevent warping and buckling of surface panels with adequate strength to withstand the imposed loads with minimal deflection when filled.
- C. Finish: Unit shall have a smooth, UV resistant, high gloss polyester gel-coat finish. Unit shall be _____ in color.

3.0 EXECUTION

3.1 INSTALLATION

Installation shall be performed by an experienced contractor according to manufacturer's instructions.

3.2 WARRANTY

The manufacturer shall provide a written five (5) year limited warranty against defects in material or workmanship.

END